

## Product Technical Data

### GUILBERT EXPRESS

10 rue Henry Delbast  
77183 Croissy-Beaubourg  
Tél : 0.825.800.251 - Fax : 0.825.800.238

Burners - Flat serie - 1660 - 1662	
Created on	16/07/2003
Modified on	23/10/2024
Issue	E

<b>Ref.:</b>	<b>1660</b>
	<b>1662</b>
<b>Name:</b>	<b>Burners - Flat serie</b>

<b>Product:</b>	<b>Burner</b>
<b>Activity:</b>	<b>Roofing</b>
<b>User:</b>	<b>Professionals - General public - DIY</b>
<b>Energy:</b>	<b>PROPANE GAS</b>

### Description

Rear air inlet nozzle (primary suction), producing excellent flame in any position, especially when directed towards the ground.

Application fields: burning, roofing, disinfection.

Gas supply from 2 to 4 bar

Stainless steel nozzle.



	<b>1660</b>	<b>1662</b>
Gas reference	Propane	Propane
Pressure	4b / 58 psi	4b / 58 psi
Gas flow	4400 g/h	10800 g/h
Power kW	60	150
BTU/h	208000	511000

<b>Spare parts</b>	<b>1660</b>	<b>1662</b>
Gas outlet Ref.	4629	4824

<b>Accessory</b>	<b>Reference</b>	<b>Length</b>
Extension	4726	40 cm
Extension	4727	20 cm

<b>Miscellaneous</b>	<b>1660</b>	<b>1662</b>
Nozzle cross-section (mm)	100 x 35	168 x 48
Flame length (mm) (3 bar)	310	600



<b>Packaging</b>	<b>1660</b>	<b>1662</b>
Weight (g)	400	620
Type	Burner hook	

### Regulation

Designed as per: EN731

Burners to be used with EXPRESS handles only.

**IMPORTANT: Read instructions before use - Use only in well ventilated areas.**

GUILBERT EXPRESS reserves the right to change product characteristics without previous notice.

Actual products may differ from photographs.

[www.guilbert-express.net](http://www.guilbert-express.net)