

Cat. No. : 445
Description : Gas cartridge

Type :

- Professional, for use with :
- Hot air gun Cat. No. 4600
 - Roofer hoseless soldering iron Cat. No. 364
 - Dehorner Cat. No. 144

Applications :

Sheet metal roofing, heat-shrinking tubes and sleeves, farming

Includes the following :

- Foam cartridge:
- Can be pointed downwards as soon as it is turned on
 - LPG + pentane mixture
 - Net gas mass : 60 g / 110 ml
 - 18-bar steel casing (recyclable)

European standard screw valve :

- 7/16" – 28 threads per inch (60 °C – 140 °F)

Use in all seasons :

- Down to -13 °C (8.6 °F) with a new cartridge

Unit weight and dimensions :

- Weight: 120 g
- Diameter: 50 mm
- Height: 180 mm

Box weight and dimensions :

- Box of 12 cartridges
- Weight: 1,5 kg
 - Width: 180 mm
 - Depth: 140 mm
 - Height: 155 mm

Recommendations :

- Single-use, non-rechargeable cartridge.
- Keep away from sunlight
- Do not expose to temperatures exceeding 50°C (122°F)
- Store in a dry, well-ventilated room

Picture :



Safety Data Sheet (SDS) :

SDS N° 010

Compliance :

NF EN 417

Barcode

3 18964000445 0

IMPORTANT: Read instructions before use

GUILBERT EXPRESS reserves the right to change products without prior notice. Actual products may differ from photographs.

www.express.fr

GUILBERT EXPRESS

10 rue Henry Delbast - 77183 Croissy-Beaubourg - Tel: 0.825.800.251 - Fax: 0.825.800.238