

**Cat. No. :** 555  
**Description :** Gas cartridge

**Type :**

- Non-professional, for use with:
- Cartridge blowtorches Cat. No. 342 / 511 / 531
- Oxy-gas sets Cat. No. 2901 / 2902 / G2903

**Applications :**

Plumbing, tin soldering, unjamming, burning.

**Includes the following :**

- LPG mixture
- Net gas mass : 340 g / 600 ml
- 15-bar steel casing (recyclable)

**European standard screw valve :**

- 7/16" – 28 threads per inch (60 °C – 140 °F)

**Use in all seasons :**

- Down to -8 °C (17.6 °F) with a new cartridge

**Unit weight and dimensions :**

- Weight: 465 g
- Diameter: 66 mm
- Height: 278 mm

**Box weight and dimensions :**

- Box of 12 cartridges
- Weight: 5,7 kg
- Width: 265 mm
- Depth: 205 mm
- Height: 290 mm

**Recommendations :**

- Single-use, non-rechargeable cartridge.
- Keep away from sunlight
- Do not expose to temperatures exceeding 50°C (122°F)
- Store in a dry, well-ventilated room

**Picture :**



**Safety Data Sheet (SDS) :**

SDS N° 004

**Compliance :**

NF EN 417

**Barcode**

3 18964000551 8

**IMPORTANT: Read instructions before use**

GUILBERT EXPRESS reserves the right to change products without prior notice. Actual products may differ from photographs.

[www.express.fr](http://www.express.fr)

GUILBERT EXPRESS

10 rue Henry Delbast - 77183 Croissy-Beaubourg - Tel: 0.825.800.251 - Fax: 0.825.800.238