

Product datasheet

GUILBERT EXPRESS

Le Pérípole, Lot 209-21033

avenue du Maréchal de Lattre de Tassigny

94127 Fontenay sous Bois Cedex

Tel: +33 (0)825 800 251 - Fax: +33 (0)825 800 238

| | |
|--------------------------------|------------|
| Roofer soldering iron type 367 | |
| Created on | 16/01/2006 |
| Modified on | 02/12/2019 |
| Issue | L |

| | |
|-----------------|--------------------------|
| Cat. No. | 367/8 - 367/9 - |
| | 6367/8 - 6367/9 - |
| | 6367/8L - 4367/8 |
| Name: | Soldering iron |

| | |
|------------------|-----------------------|
| Product: | Roofer soldering iron |
| Activity: | Sheet metal roofing |
| Users: | Professional |
| Energy: | Gas |

Description

Handle with 3/8" left-hand thread connector and Piezo ignition + roofing burner.
Compact and lightweight.
Cercoflam-type enveloping flame.
Low noise level.
Reaches operating temperature twice as fast as a conventional soldering iron.
Significant energy savings.
Tip can be rotated from 0° to 360° and tilted by ±5° for easier handling. Piezo can be changed with no tools required.
Tool supplied to change the nozzle. Steel-reinforced cast iron casing with anti-corrosion treatment.
Burner suitable for work with zinc, copper, stainless steel, pre-weathered zinc, lead, etc.
Dual-position stand with spring action.
Supply pressure: **2 bar**

Area of application:

Sheet metal roofing, zinc work, etc.



Technical data

| | Flow rate g/hr | Power | | Maximum temperature | |
|--------------------------------|-------------------|--------|------|---------------------|---------|
| | | kW | BTU | °C | °F |
| All 367-type catalogue numbers | 94 g/hr | 1.3 kW | 4400 | 600 °C | 1110 °F |

Spare parts

| | |
|-------------|------------------------|
| Tips | See datasheet for tips |
| Nozzles x 5 | Cat. No. 36713 |

Standard contents

| Cat. No. | Designation | Weight (net) |
|------------|---|--------------|
| 367/8 | Soldering iron + 678 tip | 850 g |
| 367/9 | Soldering iron + 679 tip | 930 g |
| 6367/8 | Soldering iron + 678 tip, 4.75 m hose Cat. No. 963/5, 2-bar regulator Cat. No. 682 | 1570 g |
| 6367/9 | Soldering iron + 679 tip, 4.75 m hose Cat. No. 963/5, 2-bar regulator Cat. No. 682 | 1650 g |
| 6367/8L | Soldering iron + 1778 tip, 4.75 m hose Cat. No. 963/5, 2-bar regulator Cat. No. 682 | 1560 g |
| 4367/8-V18 | Roofing burner + 678 tip | 500 g |

Materials

| |
|---|
| Tip: 99.9% pure copper |
| Burner: anti-corrosion steel-reinforced cast iron |
| Stainless steel venturi |
| Valves: brass |

IMPORTANT: Read instructions before use - For use only in sufficiently well ventilated rooms.