

**GUILBERT EXPRESS**

Le Pérépole, Lot 209-210
33 avenue du Maréchal de Lattre de Tassigny
94127 Fontenay sous Bois Cedex - France
Tel.: + 33 (0) 825 800 251 - Fax : + 33 (0) 825 800 238

Product Technical Data

Refillable gas cylinder - 7796	
Created on	05/06/06
Modified on	20/10/14
Issue	D

Ref. 7796
Name: Work site gas cylinder

Product : Work site gas cylinder
Activities: Roofing / Plumbing
User: Professional
Energy: LPG

Description - Ref. 7796

Work site refillable gas cylinder.
Contains up to 1.6 kg of butane or propane gas.
Can be easily moved everywhere on a work site.
Refillable using a standard 13 kg gas cylinder.

Warning:

Read instructions carefully before use.
Strictly obey all safety instructions.

Application fields

Roofing / Plumbing / Work site

Images**Technical features**

Capacity: 1.6 kg of propane
Empty weight: 4 kg approximately
Outlet thread: French gas cylinder (Ø 21.7 x 1.814 G, 60° profile).
Valve with bleed screw for filling and pressure relief valve.

Operating conditions

Warning: Filling must always be carried out in absolute safety conditions.
This work site gas cylinder must be used only by professionals specifically trained to properties and hazards related to LPG.

Retesting

This type of gas cylinder must be retested every 10 years.
The retesting year is printed on the the cylinder.
Contact GUILBERT EXPRESS for retesting.

Dimensions

Weight (kg)	Diameter (mm)	Height (mm)
Approximately 4 kg	202	314

Accessory(ies)

Ref. 7795 Filler tube shell

Compliance

Complies with EN 1442
Complies with European Directive 84/527/EEC. EN 442

Main materials

Body: steel
Valves and fittings: Brass

IMPORTANT: Read instructions before use

GUILBERT EXPRESS reserves the right to change product characteristics without previous notice. Actual products may differ from photographs.

www.guilbert-express.net