

GUILBERT EXPRESS

Le Péripole, Lot 209-210

33 avenue du Maréchal de Lattre de Tassigny

F- 94127 Fontenay sous Bois Cedex

Tel: +33 (0)825 800 251 - Fax: +33 (0)825 800 238

Tin solders	
Created on	11/01/2002
Modified on	15/06/2022
Issue	G

Created on	11/01/2002
Modified on	15/06/2022
Issue	G

Cat. No. Multiple references
Name : Tin solder without lead
Images
Product :
Activity :
User :
Filler metals
Multiple applications
General public / Professionals


Technical features

Conditioned by six in carton box

Cat. No.	Weight (in g)	Wire diameter (in mm)	Packaging by 6 (L x l x H en mm)	Coil (ø x H in mm)	SDS
ALL USES					
For joining copper, brass, bronze, steel, zinc and stainless steel					
Coil 96,5% tin, 3,5% silver - Incorporated flux HC3 2,4% - Melting point 221 °C - Very Fluid					
11945	40	2	170 x 55 x 40	49 x 17	328
11941	80	2	170 x 55 x 40	49 x 17	328
12940	200	2	170 x 105 x 42	49 x 37	328
5940	500	2	205 x 140 x 85	67 x 68	328
SPECIAL ELECTRICAL / ELECTRONIC COMPONENTS					
For soldering on copper, tin-plated copper and gold-nickel alloy					
Coil 99,3% tin, 0,7% copper - Incorporated flux A11 2,2% - Melting point 227 °C - Very Fluid					
11964	40	1	170 x 55 x 40	49 x 17	327
11961	80	1	170 x 55 x 40	49 x 17	327
12960	200	1	170 x 105 x 42	49 x 37	327
SPECIAL PLUMBING - SANITARY					
For joining copper and brass					
Coil 97% tin, 3% copper - Incorporated flux CR 2,2% - Melting point 310 °C - Fluid					
11894	40	2	alloy	49 x 17	327
11898	80	2	170 x 55 x 40	49 x 17	327
12890	200	2	170 x 105 x 42	49 x 37	327
5890	500	2	205 x 140 x 85	67 x 68	327
SPECIAL PLUMBING - SANITARY					
For joining copper and brass					
Coil 97% tin, 3% copper - Melting point 310 °C - Fluid					
5880	500	2	205 x 140 x 85	67 x 68	327

Accessories

Cat. No.	Description	Packaging (L x H in mm)	Application field	Braid width (in mm)
1840	Soldering liquid	30 cm ³ bottle under dual shell 70 x 130	Steel joining	-
9042	Ammoniacal stone	Dual shell 70 x 130	Stripping of soldering iron bits	-
1860	Desoldering braid, 1.5 m	70 x 130	Electronics	1,5
1850	Desoldering braid, 1.5 m	70 x 130	Radio-Electricity	3

Others

Certification:

NFC 90 550