

GUILBERT EXPRESS

Le Pérépole, Lot 209-210
33 avenue du Maréchal de Lattre de Tassigny
94127 Fontenay sous Bois Cedex
Tél : 0.825.800.251 - Fax : 0.825.800.238

Blowlamp - 8200	
Created on	23/03/2021
Modified on:	08/04/2021
Issue	A

Ref.	8200
Name	Blowlamp

Product :	Cartridge blowlamp
Activity :	Multipurpose
User :	General public and Professionals
Energie :	Butane gas, 1.5 bar


Description

Knob for gas flow on/off and adjustment.
Plastic bell with locking clip.
Piezo ignition.

Application fields

Plumbing, brazing, stripping, loosening of bolts and nuts, burning...

Flame type :	Sharp tip
Flame dimensions :	Dia. 6 x 60mm
Nozzle inner diameter:	Dia. 16mm
Flame length :	170mm



Functions

Flame : Sharp tip
Gas flow on/off and adjustment (knob)
Flame adjustment (knob)
Piezo ignition (button)
Base (bell jar)
Working upside down : 1 min 30 sec

Technical features

Flow (g/h) at 1.5 bar	116
Power (kW)	1,60
Autonomy (hours)	1h30
Flame temperature (°C) (approximately)	1850°

To be used only with EXPRESS butane gas cartridges Ref. 8191

Soldering capacity on copper tubes

	Dia. (mm)
Cu Ph	Dia. 14
Etain 40%	Dia. 14
Cu Ph 30% Ag	Dia. 16
Sn 97% Cu 3 %	Dia. 50

Packaging

	Poids (g)	Larg.(mm)	Prof.(mm)	Haut.(mm)
Appareil conditionné "Boîte en carton"	460	210	110	165
Surconditionnement (24 pièces)	11 040			

IMPORTANT : Read instructions before use.

GUILBERT EXPRESS reserves the right to change product characteristics without previous notice. Non-contractual photos.

www.guilbert-express.net