

# Sticks of solder

**CAT. NO. GE168B**

## AREAS OF APPLICATION



Plumbing / Sanitary applications

Joining types  
**Copper /  
Copper**

For brazing joints with  
**standard clearances**  
**(0.05 to 0.1 mm**  
**0.002 to 0.004 in)**

Working temperature  
**730 °C / 1346 °F**  
Melting range  
**710 °C - 815 °C**  
**1310 °F - 1499 °F**

Soft case  
**1 kg / 2.20 lb**



## TO BE USED WITH:



Soldering paste  
**Cat. No. GE6GFA**

**Small format**  
Ideal for odd  
brazing jobs



Soldering powder  
**Cat. No. GE6PFA**

L **500 mm**  
**19.68 in**  
Ø **2 mm**  
**0.08 in**

Copper  
Phosphorus  
**6.8 %**

Mechanical  
resistance  
**45**  
**daN/mm<sup>2</sup>**

**Standard**  
fluidity

Made in France

Cat. No.	Product title	Nbr. units	EAN
<b>GE168B</b>	<b>Sticks of solder</b>	<b>1</b>	<b>3189640016835</b>

## Guilbert Express

ZAE de Lamirault - 10 rue Henry Delbast - 77183 Croissy-Beaubourg

Adresse de correspondance : ZAC de Lamirault - 10 rue Henry Delbast - CS 20955 - 77437 Mame la Vallée CEDEX 02

Tél. : 0825 800 251 - Fax : 0825 800 238 - www.express.fr - info@express.fr



@guilbertexpress



@guilbert.express.official



@ExpressFrance

